

WEST WING GEOTHERMAL PRESENTATION

ENGR 333

DECEMBER 4, 2012

SPOELHOF CENTER WEST WING ADDITION



Introduction

Energy Modeling

Infrastructure

Below Ground


Above Ground

Financial

Recommendation

LOCATION

Proposed West Wing Addition



Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

HOW DOES GEOTHERMAL WORK?



<http://www.drenergysaver.com/renewable-energy/geothermal-heat.html>

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

GEOHERMAL BENEFITS AND COSTS

Benefits

- Reduced energy consumption
- Reduced maintenance

Costs

- More complex
- Installation

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

PROJECT OVERVIEW

- Objective:
 - As a class we are to determine what it would take to use a geothermal Heating, Ventilation, and Air Conditioning (HVAC) system in the West Wing Addition
- 5 groups for analysis
 - LEED & Energy Modeling
 - Infrastructure
 - Below Ground
 - Above Ground
 - Financial

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

LEED & ENERGY MODELING

Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

TEAM MEMBERS



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

KEY QUESTIONS

- How will a geothermal system contribute to achieving LEED certification?
- What are the heating & cooling loads for the West Wing addition?

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

LEED RATING SYSTEM

- LEED = Leadership in Energy and Environmental Design
- Aiming for LEED silver rating, according to Henry DeVries
 - Requires 50-59 points out of possible 110 points



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

LEED POINT CATEGORIES

- 6 categories
 - Sustainable Sites
 - Water Efficiency
 - Energy and Atmosphere
 - Materials and Resources
 - Indoor Environmental Quality
 - Innovation in Design



LEED Core Concepts and Strategies Online Course

Introduction

Energy Modeling

Infrastructure

Below Ground


Above Ground

Financial

Recommendation

ENERGY CONSUMPTION BREAKDOWN

Heating and Cooling accounts for approximately 34% of a building's energy usage



US Energy Information Administration

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

ON-SITE RENEWABLE ENERGY LEED POINTS

Percentage Renewable Energy	Points
1%	1
3%	2
5%	3
7%	4
9%	5
11%	6
13%	7

From LEED 2009 for New Constructions and Major Renovations

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

IMPORTANCE OF HEATING/COOLING LOADS

- “Load” is the heat that must be removed in the summer and added in the winter.
- Prevent oversized/undersized HVAC system
- Directly affect the progress of other teams.

Introduction

Energy Modeling

Infrastructure


Below Ground

Above Ground

Financial

Recommendation

HEAT LOSSES



<http://www.momgoesgreen.com/keeping-warm%E2%80%A6-while-staying-green/>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

CALCULATION METHOD

Started with calculations from KHvR
geothermal suite

Made additions

```

Heating Load of a suite in the KH residence hall addition

The purpose of this worksheet is to calculate the heating load of a first floor suite in the Residence Hall addition to Kalsbeek/Huizenga Hall of Calvin College.

...HEAT LOSS THROUGH EXTERIOR WALL...
Temperatures
T_i = converttemp(F,R,72[F]) "inside room temperature"
T_o = converttemp(F,R,0[F]) "outside ambient temperature"
T_inf = converttemp(F,R,0[F]) "temperature at infinity for radiation heat transfer"

areas
A_wallframe = (31+10/12)*8[ft^2]
A_wall = A_wallframe - A_window
A_window = 8*4[ft^2]

Thermal resistances of outer wall
R_facebrick = 0.45[ft^2-hr-F/BTU] "exterior face brick"
R_foam = 12[ft^2-hr-F/BTU] "2 inch rigid foam insulation"
R_CMUbrick = 1.11[ft^2-hr-F/BTU] "8 inch C.M.U. brick"
R_window = 8[ft^2-hr-F/BTU] "double paned air gap with .75in air gap"
R_air = 0.25[ft^2-hr-F/BTU] "outside air"
R_lair = 0.25[ft^2-hr-F/BTU] "inside air"
R_wall_tot = R_oair+R_facebrick+R_foam+R_CMUbrick+R_lair
R_window_tot = R_oair+R_window+R_lair


radiation heat transfer
f = 1 "view factor of wall to sky"
gma = (5.67*10^-8) [W/m^2-K^4] convert(W/m^2-K^4, BTU/hr-ft^2-R^4) "Stephon-Boltzman constant"
epsilon_facebrick = .75 "emissivity of exterior face brick"
epsilon_window = .94 "emissivity of window"
Q_dot_rad_wall = epsilon_facebrick * A_wall * F * sigma * (T_i^4 - T_o^4) "radiative heat transfer to wall"
Q_dot_rad_window = epsilon_window * A_window * F * sigma * (T_i^4 - T_o^4) "radiative heat transfer to window"

convective heat transfer
Q_dot_conv_wall = A_wall * (T_o - T_i) / R_wall_tot "heat transfer through the wall"
Q_dot_conv_window = A_window * (T_o - T_i) / R_window_tot "heat transfer through the window"

total heat transfer
Q_dot_heatloss = Q_dot_conv_wall + Q_dot_conv_window + Q_dot_rad_wall + Q_dot_rad_window "total heat transfer from exterior wall/window"


...OUTSIDE AIR LOADS...
Q_dot_outsideairloads = -000[BTU/hr] "total heat transfer from outside air loads"
we're considering this to be negligible since the air will be contained in the entryway and lobby of the building

...OCCUPANT LOADS...
Q_dot_person = 411[BTU/hr]
    
```




```

...INTRODUCTION...
...BUILDING...
...TEMPERATURES...
...THERMAL RESISTANCES OF WALLS...
...RADIATION HEAT TRANSFER...
...CONVECTIVE HEAT TRANSFER...
...TOTAL HEAT TRANSFER...
...OUTSIDE AIR LOADS...
...OCCUPANT LOADS...
    
```



DAILY HEATING & COOLING REQUIREMENTS



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

HEATING & COOLING LOADS BEST ESTIMATE

- Heating: 174 Tons
- Cooling: 86 Tons
- Tons are a standard unit of heating and cooling: 1 ton = 12,000 Btu/hr

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

FINAL ANSWERS

- How will a geothermal system contribute to achieving LEED certification?
 - 7 points towards the goal of 50
- What are the heating & cooling loads for the West Wing addition?
 - Heating: 174 Tons
 - Cooling: 86 Tons

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

INFRASTRUCTURE

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

TEAM MEMBERS



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

KEY QUESTIONS

- How will the geothermal system fit in at Calvin College?
- What type of loop configuration will be used?
- Where will the geothermal ground loop be located?

Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

INTEGRATED SYSTEM



Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

STAND ALONE SYSTEM



Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

POND LOOP



<http://www.fhp-mfg.com/files/images/common/coupCx03.jpg>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

CAMPUS MAP

Building Addition

Pond Loop



Introduction

Energy Modeling

Infrastructure


Below Ground

Above Ground

Financial

Recommendation

HORIZONTAL LOOP



<http://www.fhp-mfg.com/files/images/common/coupCx02.jpg>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

CAMPUS MAP

Horizontal Loop



Building Addition



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

VERTICAL LOOP



<http://www.fhp-mfg.com/files/images/common/coupCx01.jpg>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling


Below Ground

Financial

CAMPUS MAP

Building Addition

Vertical Loop



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Recommendation

Financial

ANSWERS

- How will the geothermal system fit in at Calvin College?
 - Mechanical Separation
- What type of loop configuration will be used?
 - Vertical
- Where will the geothermal ground loop be located?
 - West Parking Lot

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

BELOW GROUND

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

TEAM MEMBERS



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

KEY QUESTIONS

- What is the Design of the Borefield?
 - How many bores?
 - How deep?
 - How far apart?
 - Will local geology affect the design?
 - How much will it cost?
 - How long will it last?

Introduction

Infrastructure

Above Ground



Recommendation

Energy Modeling

Below Ground

Financial

KH_vR GEOTHERMAL INSTALLATION



<https://maps.google.com/maps?q=calvin+college&aq=f&sugexp=chrome,mod%3D0&um=1&ie=UTF-8&hl=en&sa=N&tab=wl>

Cleanly Cooling Calvin (Senior Design 2008)

Introduction

Infrastructure

Above Ground

Recommendation


Energy Modeling

Below Ground

Financial

THERMAL MODELING - INITIAL

- Factors to account for:
 - Temperature Gradient vs. Constant Ground Temperature
 - Soil Composition/Location



<http://www.geo4va.vt.edu/A1/A1.htm>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

THERMAL MODELING - INITIAL SUMMARY

- Heating Load: 140 ton
- Borehole Depth: 300 – 420 feet
- Number of Boreholes: 175 – 200

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

REFINED BOREFIELD DESIGN



<http://mwgeothermal.com/>

Introduction

Infrastructure

Above Ground

Recommendation


Energy Modeling

Below Ground

Financial

REFINED BOREFIELD DESIGN

- Thermal Conductivity: 1.35 Btu/hr-ft-°F
- Operating Fluid: Water/Glycol Mix
- Bore Feet needed to accommodate loads
 - 28,447 feet
- Effective Bore Feet
 - 33,180 feet



<http://www.xydatasource.com/xy-showdatasetpage.php?datasetcode=234654&dsid=67>

Introduction

Infrastructure

Above Ground

Recommendation


Energy Modeling

Below Ground

Financial

PROPOSAL

- What is the Design of the Borefield?
 - How many bores?
 - **88 bore holes**
 - How deep?
 - **400 feet deep (L_B)**
 - How far apart?
 - **20 feet center-to-center (S_B)**
- Additional Details:
 - 5 inch bores (D_B)
 - 1.25 inch HDPE pipe



REFINED BOREFIELD DESIGN

- How much will it cost?
 - Total Installation Costs = **\$478,720**
 - \$13.60/bore feet
 - Pipe Costs
 - Site Costs
- How long will it last?
 - Economic Life
 - **50 years**

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

ABOVE GROUND

A thin, horizontal orange glow line is positioned directly below the text "ABOVE GROUND". The glow is centered and tapers slightly towards the edges, creating a subtle light effect against the dark background.

TEAM MEMBERS



Introduction

Infrastructure

Above Ground

Recommendation

~~Energy Modeling~~

~~Below Ground~~

Financial

KEY QUESTIONS

- What system should be selected to meet the HVAC demands of the new addition?
 - Water to Air vs Water to Water?
 - Centralized vs Distributed System?
 - Energy Recovery Ventilation?

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

SYSTEM REQUIREMENTS

- Heating/Cooling Loads
 - Heating Load: 174 Tons
 - Cooling Load: 86 Tons
- Ventilation Requirements
 - Estimated Air Flow Required: 48,000 cfm
 - Michigan Mechanical Codes/ASHRAE Standards

Figure 6: Excerpt from Table 2 of ASHRAE Standard 62-2001

Application	Estimated Maximum Occupancy (people/1000 ft ²)	Outdoor Air Requirements	
		cfm/person	cfm/ft ²
Offices			
Office space	7	20	
Reception areas	60	15	
Telecommunication centers and data entry areas	60	20	
Conference rooms	20	20	

trane.com/commercial/uploads/pdf/520/ISS-APG001-EN.pdf

Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

WATER TO AIR vs WATER TO WATER SYSTEMS



- Ventilation System
- Lower Cost

Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

WATER TO AIR vs WATER TO WATER SYSTEMS



- Ventilation System
- Lower Cost

- Air Handlers and Radiators
- Higher Cost

Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation


CENTRALIZED vs DISTRIBUTED SYSTEMS



http://csmdetroit.com/yahoo_site_admin/assets/images/3200_8.345123502_large.jpg



<http://4mechanical.com/wp-content/uploads/2011/09/Ductwork1.jpg>



<http://www.geo4va.vt.edu/A3/A3.htm>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

HEAT PUMP SELECTION



<http://www.carrier.com/>

\$1,200,000



<http://www.mammoth-inc.com/>



<http://www.trane.com/>

\$840,000

Introduction

Infrastructure

Above Ground

Recommendation


Energy Modeling

Below Ground

Financial

DUCTWORK

- Estimated Length of Ducts Required: 5800ft
 - Cost of Installation and Purchase: \$54,000



Ductwork diagram (third floor)

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

ENERGY RECOVERY VENTILATION (ERV)

- Ventilation unit that preheats or precools incoming air using exiting air streams
 - Increases efficiency of the system by roughly 20%
 - Additional cost: \$400,000



<http://www.renewaire.com/index.php/products/commercial-products/he8xrt>

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

RECOMMENDATION

- Centralized, Water to Air System
- 175 Ton rooftop heat pump (Trane)
- Energy Recovery Ventilation System
- Total Cost: \$1,300,000



Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

FINANCIAL GROUP

TEAM MEMBERS



Introduction

Energy Modeling

Infrastructure

Below Ground

Above Ground

Financial

Recommendation

KEY QUESTION

Is a geothermal system a financially viable option for the West Wing addition?

Introduction

Energy Modeling

Infrastructure


Below Ground

Above Ground

Financial

Recommendation

NATURAL GAS PRICES



http://www.eia.gov/forecasts/archive/aeo11/source_natural_gas.cfm

- 2012-2035: Data from Department of Energy
- 2035- : Data projected based on best-fit trends

Introduction

Energy Modeling

Infrastructure


Below Ground

Above Ground

Financial

Recommendation

ELECTRICITY PRICES



<http://www.eia.gov/oiaf/aeo/tablebrowser/#release=AEO2012&subject=0-AEO2012&table=8-AEO2012®ion=0-0&cases=ref2012-d020112c>

- 2012-2035: Data from Department of Energy
- 2035- : Data projected based on best-fit trends

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

INITIAL COSTS

Geothermal System		Conventional HVAC System	
Initial Costs		Initial Costs	
Borefield Cost	\$ 478,720	Ductwork Cost	\$ 53,806
Piping/Pumps Cost	\$ 10,000	Air Handler Cost	\$ 150,000
Heat Pump Cost	\$ 1,240,000	Total Cost	\$ 203,806
Total Cost	\$ 1,728,720		

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

ENERGY COSTS

- **GEOHERMAL**

- Based on Heating/Cooling Loads and pump usage
- Total Energy Required: **562,040 (kWh/yr)**

- **CONVENTIONAL HVAC**

- Heating Load: 7,316 (MMBtu/yr)
- Cooling Load: 143,808 (kWh/yr)
- Total Energy Required: **2,288,350 (kWh/yr)**

Geothermal Heating COP	3.68
Geothermal Cooling EER	21.39

Conventional HVAC Heating Eff.	80%
Conventional HVAC Cooling EER	10

<http://www.duke-energy.com/pdfs/110371-HVAC-Whitepaper.pdf>

Introduction

Infrastructure


Above Ground

Recommendation

Energy Modeling

Below Ground

Financial



(optimistic economic conditions)

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

MAINTENANCE COSTS

- **GEOHERMAL**

- **\$9,000 per year** (ASHRAE)
- Heat Pump replacement after 20 yrs.

- **CONVENTIONAL HVAC**

- **\$15,000 per year**
- Air Handler replacement after 20 yrs.

Annual Maintenance (\$/yr)	9000
Later Maintenance (\$/yr)	13500
Heat Pump Replacement Cost (\$)	336000

Annual Maintenance (\$/yr)	15000
Later Maintenance (\$/yr)	22500
Air Handler Replacement Cost (\$)	150000

Later Maintenance: costs increase by 50% after 10 yrs.

Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

Cumulative Costs



Introduction

Infrastructure

Above Ground


Recommendation

Energy Modeling

Below Ground

Financial

Cumulative Costs (High Natural Gas Prices)



Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

FINANCIAL PROPOSAL

- As Christians, we have a calling to be stewards of Creation and Money
(Luke 14:28-30, 1 Corinthians 4:7)
- There is no foreseeable financial payback
- From a solely financial standpoint, the financial group recommends a geothermal system not be constructed until such time as:
 - Natural gas prices rise dramatically
 - Entire campus considered

Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

FINAL RECOMMENDATION – ENGR. 333 CLASS

Geothermal Advantages

- Reduce energy costs
- Lower maintenance costs
- Promotes stewardship of creation
- Contributes to LEED certification
- Small scale example of possible campus wide geothermal
- Enhancement of college image

Geothermal Disadvantages

- High initial cost
- Additional construction site – well field
 - Coordinate with parking lot construction

Proposal: Utilize existing HVAC system

ACKNOWLEDGEMENTS

Class Advisors

- Trent DeBoer
- Henry DeVries
- Professor Heun
- Paul Pennock

Additional Help


- Phil Beezhold
- Scott Skoog & Kortney Lull, Midwest Geothermal
- Dan Pabst
- Dean Anderson
- Dan Slager

QUESTIONS

HEAT GAINS

- Several factors also provide heat gain to a building
 - Occupants (1 person produces around 400 BTU/day)
 - Equipment in rooms (computers, projectors, etc)
 - Lighting

Heat Gains



Introduction

Infrastructure

Above Ground

Recommendation

Energy Modeling

Below Ground

Financial

EXTERNAL FUNDING

- Direct external funding (tax refunds/incentives) are unavailable as Calvin College is a tax-exempt entity
- However, according to Scott Skoog of Midwest Geothermal, indirect incentives are a possibility.
- In this case, an architect/engineering firm can apply for a tax deduction for designing or building an energy saving building for a non-profit or government agency.
- In this way, the firm saves money on designing/building Calvin's geothermal, and partially passes these savings on to Calvin.

CALVIN ENERGY RECOVERY FUND (CERF) UTILIZATION

- CERF is a revolving fund used to improve energy efficiency and decrease carbon emissions.
- CERF is currently growing by investing in smaller scale projects (lighting, computer shutdown)
- The scale of this project vs. CERF's budget (~\$65,000) seems to be a bad fit.
- Recommendation: Don't utilize CERF in this project